


TYPICAL BENCHING ON EXISTING EMBANKMENT




REVISED - 2-22-06

TYPICAL BENCHING ON EXISTING EMBANKMENT

50.4

LAND SECTION & REFERENCE MARKERS




METHOD OF REFERENCING POINTS

REFERENCE MARKERS SHALL BE USED TO TIE IN PERMANENT LAND SECTION AND 1/4 SECTION CORNERS. WHERE LAND SECTION MARKERS FALL IN THE SHOULDERS OR GRAVEL SURFACES, THE TOP OF THE BAR SHALL BE KEPT 75(3) BELOW THE SURFACE. LAND SECTION MARKERS LOCATED IN TRAFFIC LANES SHALL NOT BE REPLACED.

METAL CAPS SHALL BE PLACED ON TOP OF THE REINFORCEMENT BAR. THERE ARE 3 TYPES OF CAPS, ONE FOR THE RIGHT-OF-WAY CORNERS, ONE FOR THE SECTION CORNERS AND ONE FOR THE SECTION CORNER TIE POINTS. THE CAPS WILL BE SUPPLIED BY IDOT, CALL CHIP CORDELL (815) 284-5370 A MINIMUM OF ONE WEEK BEFORE THE CAPS ARE NEEDED

METHOD OF REFERENCING MARKERS



- USE INSTRUMENT TIES TO NEARBY LAND-MARKS (STEEPLES, TOWERS, SILOS, ETC...) IN CULTIVATED FIELDS, SET 600(2')
- OR MORE BELOW GROUND SURFACE.
- IN FENCE LINE OR PROTECTED AREA SET TOP AT GROUND LEVEL.

ALL DIMENSIONS ARE IN MILLIMETERS (INCHES) UNLESS OTHERWISE NOTED.

REVISED - 1-22-07

STOP LINE SIGN FOR TEMPORARY SIGNALS



SIZE: $600(24) \times 600(24)$

100(4) CAPITAL LETTERS - BLACK

13(1/2) BORDER - BLACK

WHITE REFLECTIVE - TYPE AP HIGH INTENSITY PRISMATIC SHEETING

GENERAL NOTE:

THIS SIGN SHALL BE INSTALLED AT THE STOP LINE AS DIRECTED BY ENGINEER.

ALL DIMENSIONS ARE IN MILLIMETERS (INCHES) UNLESS OTHERWISE NOTED.

LAND SECTION & REFERENCE MARKERS

STOP LINE SIGN FOR TEMPORARY SIGNALS

99.4

TILE NAME DESIGNED - JMS REVISED SER NAME = HAS 264AØ4-sht-detailsØ8.dor DRAWN REVISED STATE OF ILLINOIS

DISTRICT 2 STANDARDS SCALE: NO SCALE SHEET NO. 2 OF 8 SHEETS STA.

COUNTY 638 HENRY CONTRACT NO. 64A04

OT SCALE = 0.0833 '/ IN. REVISED DATE 07/17/09 REVISED

DEPARTMENT OF TRANSPORTATION

63.4